

WORKSAFE 2206 LED

THE WORKSAFE LANTERN CAN BE USED IN HAZARDOUS ATMOSPHERES AND CARRIES A 150 HOUR RUNTIME

- Intrinsically Safe
- Waterproof, IP67 rating
- D' Cell Alkaline Batteries
- Switch Guard protects switch on impact
- Glove friendly handle



LIGHTWEIGHT, WATERPROOF, AND AFFORDABLE CLASS 1, DIVISION 1 LANTERN

FL1 STANDARDS














SPECIFICATIONS

POWER SOURCE: 4D-Cell alkaline batteries

LIGHT SOURCE: LED **LIGHT OUTPUT**: 90 Lumens

PEAK BEAM INTENSITY: 7,000 candela

BEAM DISTANCE: 165 Meters **RUN TIME:** 150 Hours

MASTER PACK

WEIGHT: 14.66 oz without batteries

LENGTH: 8.2 in. **WIDTH:** 4.9 in. **Height:** 5.6 in. **COLORS:** Safety Orange, Black Lens Rim

SAFETY RATINGS

UL protection Methods UL 913 CSA C22.2

Intrinsically Safe Division 1 and 2 Class I, II, III Div 1 Groups A-G Class I, II, III Div 2 Groups A-G

Operating Temp T5

*Safety ratings approvals based on Duracell MN1300 or Energizer E95 cells only



