




PRODUCT INFORMATION

DuPont™ Tychem® 2000 Coverall. Standard Fit Hood. Stormflap. Elastic Wrists and Ankles. Serged Seams. Pin Lock Slider Zipper Pull. Yellow.

ATTRIBUTES

Full Part Number	QC127SYLxx0012yy (xx=size;yy=option code) ?
Fabric/Materials	TYCHEM® 2000
Design	Coverall w/ Hood, Elastic Wrists and Ankles
Seam	Serged
Color	Yellow
Quantity/Box	12 per case
Sizes	MD, LG, XL, 2X, 3X, 4X, 5X, 6X, 7X
Option Codes	00




SIZE TABLE

SIZE	SLEEVE LENGTH	CHEST WIDTH	INSEAM	FITS CHEST	FITS HEIGHT
MD	33 3/4	24 1/4	27 1/2	35 1/4 - 38 3/4	5'3" - 5'7"
LG	35	25 3/4	28 1/2	38 1/4 - 41 3/4	5'5" - 5'9"
XL	36 1/2	27 1/4	29	41 1/4 - 44 3/4	5'8" - 6'2"
2X	38 1/4	28 3/4	30	44 1/4 - 47 3/4	6'0" - 6'4"
3X	38 1/2	30 1/4	31	47 1/4 - 50 3/4	6'2" - 6'4"
4X	39 1/2	32	32	50 3/4 - 54 1/4	6'4" - 6'7"
5X	40 1/2	33 1/2	33	53 3/4 - 57 1/4	6'7" - 6'10"
6X	41 1/2	35 1/2	34	57 3/4 - 61 1/4	6'9" - 7'1"
7X	42 1/2	37	35	60 3/4 - 64 1/4	7'0" - 7'4"

## TECHNICAL DATA SHEET

### PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULT
Thickness	ASTM D1777	10 mils
Basis Weight	ASTM D3776	2.5 oz/yd <sup>2</sup>
Burst Strength - Mullen	ASTM D3786	68 psi
Tear Resistance - Trap Tear (MD)	ASTM D5587	6.4 lb <sub>f</sub>
Tear Resistance - Trap Tear (CD)	ASTM D5587	5 lb <sub>f</sub>
Breaking Strength - Grab (MD)	ASTM D5034	39 lb <sub>f</sub>
Breaking Strength - Grab (CD)	ASTM D5034	43 lb <sub>f</sub>
Wearing Apparel Flammability	16 CFR 1610 	Class 1

### WARNING

\*Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.

\*CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for informational use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact DuPont for specific data. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including, without limitation, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or its use.

Cellosolve® and Selexol™ are registered trademarks of Dow Chemicals Company. Skydrol® is a registered trademark of Solutia.

Tyvek® 500, Tyvek® 600, Tyvek® 800 products manufactured before January 2023 did contain natural rubber latex which may cause allergic reactions in some sensitized individuals. Anyone who begins to exhibit an allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at +1 (888) 439-2988 so that an investigation can be initiated.

For further product information, literature and as well as assistance in locating a local supplier, please visit: [www.unisafeservices.com](http://www.unisafeservices.com)

### Unisafe Services

201, Tithi Complex, 75 Sampatrao Colony, BPC Road, Alkapuri,  
Vadodara - 390 007. Gujarat. India.  
Tel.: 91-7069699935, 9427602166, 9173191372  
E-mail: [sales@unisafeservices.com](mailto:sales@unisafeservices.com)