

RESPONDER PRO RIGHT ANGLE

Item# 520304 | Alkaline Responder LED

UPC# 01673152304













Extreme Smoke Cutting Beam Strength With Industry Leading 52,500 Candela



Proudly designed, engineered, and made
in **Pennsylvania, USA** with domestic
and globally sourced components.

- 10% Brighter beam than previous industry-leading Right Angle light
- Slim profile design keeps light close to your body to prevent entanglement
- High/Low beams available for up to 14 hours runtime
- Strobe - Emergency Lighting mode
- Wide-eye lens
- Oversized Pushbutton Switch for Gloved Hands
- Waterproof to one meter
- Super tough nylon construction
- Spring loaded polymer clip
- Withstands a 4m Drop
- Screw insert for accessories & additional mounting options
- Allows user to switch power supply from (4) AA alkaline batteries to Rechargeable Li-ion pack.

**PIERCES THROUGH SMOKE,
DUST AND DARKNESS TO A
DISTANCE OF 458 METERS!**

High Mode		Low Mode	
FL 1 STANDARD		FL 1 STANDARD	
 275 LUMENS	 8 h	 165 LUMENS	 14 h
 52,500cd	 4m	 31,500cd	 4m
 458m	 1m	 354m	 1m

Specifications

Power Source: 4 AA Batteries
Light Source: Advanced LED Technology
Light Output: 275lm (high) / 165lm (low)
Peak Beam Intensity: 52,500cd / 31,500cd
Beam Distance: 458m (high) / 354m (low)
Run Time: 8 Hours (high) / 14 Hours (low)
Weight: 13oz with 4 AA Alkaline Batteries
Length: 7.2in. **Width:** 3.2in. **Depth:** 1.8in.
Color: High-Vis Green

Safety Ratings

Intrinsically Safe
 UL Protection Methods
 UL 913 CSA C22.2 No 157
 Class I, II, III, Division 1, Groups C - G
 Class I, II, III, Division 2, Groups C - G
 Operating temp code T3
 NFPA 70 504.2 (2008)
 NFPA 1901-14.1.11.2 (2009)
 Certified Mounted in any Position

Address: 201, Tithi Complex, 75 Sampatrao Colony, BPC Road, Alkapuri, Vadodara - 390 007. Gujarat. India.

WHAT'S INCLUDED:

- Responder PRO Right Angle Flashlight
- Alkaline Battery Tray

To upgrade from Alkaline to Rechargeable Model, you'll need to add an optional charger, rechargeable battery, and a plug.

ACCESSORIES:

- 10B-2298 — Charger Base Only
- 3B-2291 — Rechargeable Battery
- 3B-2295 — Alkaline Battery Tray
- 20638 — 12/24V DC Plug
- 20628 — 120V North American Plug
- 20629 — 208/240V Euro Plug
- 20627 — 208/240V United Kingdom Plug
- 3B-2033 — Direct Wire



Address: 201, Tithi Complex, 75 Sampatrao Colony, BPC Road, Alkapuri, Vadodara - 390 007. Gujarat. India.